



Hardwired AC Surge Protection

CM160



The CM160 Series is a high performance surge protector designed for critical panel locations. The SPD incorporates high-energy MOVs with EMI/RFI noise filtering to provide protection against transients originating from induced lightning strikes and utility switching.

Real-time diagnostics include LED fault indicators for each phase as well as the presence of abnormal voltages between the neutral to ground mode, where applicable. Form C dry contacts for remote indication and an audible alarm ensure the CM160 Series is always at full capacity.

Housed in a rugged NEMA 4X enclosure these devices are suitable for harsh indoor or outdoor applications. The CM160 Series is available for all voltages and configurations up to 277/480Vac.

AC Panel Protection

- 160kA transient amps protection (8/20µs)
- All modes of protection
- Full On-Board Diagnostics— LED indicators, remote, surge counter & audible alarms.
- 200kAIC Fault Current Rated
- Integral Fused Disconnect
- EMI/RFI Noise Filtering (-40dB)
- NEMA 4X enclosure
- 10-Year warranty

Characteristics

Surge Handling (I _{max})	160kA/phase
Protection Modes	L-N, L-G, N-G, L-L
EMI/RFI Noise Rejection	-40dB
LED Indicators	Fuse or Power Loss
Audible Alarm	Yes
Remote Signalling	Form C dry contacts
Connecting Wire Size	#2-10 AWG
Response Time	<5 nanoseconds
Dimensions	15" x 11" x 4.5"
Enclosure	NEMA 4X, PC
Weight	12lbs

Standards & Guidelines

UL 1449 2nd Edition	USA
IEC 61643-11	International
ANSI/IEEE C62.41	USA
NFC 61740-95	France
VDE0675-6	Germany
CSA C22.2	Canada
CE Marked	European

Model	Configuration	UL1449 500A				Joules	MCOV
		L-N	L-G	N-G	L-L	(10/100us)	
CM160-120T	120/240Vac, 1ph, 3W+G, split phase	500	800	500	800	3,960j	150V
CM160-120Y	120/208Vac, 3ph, 4W+G, wye	500	800	500	800	4,680j	150V
CM160-220Y	220/380Vac, 3ph, 4W+G, wye	1000	1000	1000	1800	8,320j	320V
CM160-240Y	240/415Vac, 3ph, 4W+G, wye	1000	1000	1000	1800	8,320j	320V
CM160-240DCT	120/120/240Vac, 3ph, 4W+G, hi-leg	500	800	500	1800	5,800j	150/320V
CM160-240D	240Vac, 3ph, 3W+G, delta	-	1000	-	1800	7,680j	320V
CM160-277Y	277/480Vac, 3ph, 4W+G, wye	1000	1000	1000	1800	8,320j	320V