



PRICE LIST

Effective: May 1, 2021

800-234-1343

2915 Parkway Street - Lakeland, FL 33811

www.wici.com

sales@wici.com



To Order Call: 800-234-1343 or 863-647-2000

Prices and Specifications subject to change without notice. Prices F.O.B. Lakeland, FL

©2021 by WILKERSONINSTRUMENTCO.,INC.

TERMS AND CONDITIONS OF PURCHASE

2021 marks the 38th year Wilkerson Instrument Company has produced industrial grade process control instrumentation. It is our mission at our facility to produce the highest quality, most reliable products possible at a reasonable price and follow up that commitment with superior customer service, application support and outstanding warranty coverage. This is all part of the total package Wilkerson Instrument Company provides our customers with each and every purchase.

FAST DELIVERY

Most orders are shipped in three (3) business days WITH NO HANDLING OR EXPEDITING CHARGES EVER. Delivery times will vary depending on the ship method chosen and customer's geographic location. Large quantities and special orders may require more time. Be sure to ask your sales representative if you require expedited service or need to request a specific ship date.

SHIPMENTS

Standard shipments are UPS Ground at our volume discounted rates. All other UPS services are also available, should you need expedited delivery. Fed Ex., DHL, and USPS are available if requested. Any of these services can be C.O.D. at additional cost.

TERMS

Terms of payment include;

- 1%15, Net 30 days from invoice date for open account customers.
- MasterCard, Visa, Discover and American Express are accepted for your convenience.
- All prices are quoted F.O.B. Lakeland, Florida, USA.

PRICES AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

CANCELLATION OF ORDERS AND RESTOCKING

In most cases, our "expedited" shipment commitment requires that we start manufacturing your order the day we receive it. Please be sure of your needs and specifications before ordering.

All returned orders are subject to a restocking charge of 20%, plus 10% per month from the Wilkerson Instrument Co., Inc. invoice date.

"Specials" cannot be returned for credit.

Scheduled orders with requested ship dates cancelled 5 business days or less before scheduled shipment are subject to a cancellation charge of 20%.

NEW CUSTOMERS

New customers desiring to open an account should supply:

- Three "trade" credit references.
- Bank reference, account number and contact information.
- Names of Accounts Payable Supervisor and Controller.

Credit checks are usually done by fax and require approximately three (3) business days.

DOCUMENTATION

Each product is shipped with appropriate information for installation, operation, and calibration. Please contact the factory regarding any inquiries or additional questions you may have. All documentation can be downloaded from www.wici.com.

TABLE OF CONTENTS

	PAGE
Terms and Conditions	2
MIGHTY MODULE Series	
Mighty Module Transmitters	4
Mighty Module Alarms	5
Plug In Modules	
FR Series (Field Rangeable Alarms)	
FR Series	5
DIN Rail Mounted	
DIN/MOD Series	6
DR Series	6
Digital Process Indicators	
DIS Series I	6
DIS Series II	7
LP400 Loop Powered Series	7
Two Wire Transmitters	
SF1000 Series	8
SR2000 Series	8
TW300 Series	8
Level Monitor and Control	
LM1000 Series	9
LS1000 Level Sensor	9
MOSCAD Interface Products	
SIB-V245/V453	9
SIB-MCE-T1	9
Wireless Signal Conditioners / Alarms	
DR Series	9
DR Series Antennas	10
DR Series Accessories	10
DR Series Enclosures	10
Customer Service and Warranty Policy	11

MIGHTY MODULE

SERIES SIGNAL CONDITIONERS



PLUG-IN PRODUCTS		PRICE
MM3200	Valve controller	\$ 330
MM4001	RTD transmitter	325
MM4001ISO	Isolated RTD transmitter	400
MM4003	Potentiometer transmitter	285
MM4003ISO	Isolated Potentiometer transmitter	365
MM4010	DC transmitter	245
MM4010WR	DC transmitter, wide-ranging	285
MM4050	Low input DC transmitter, <50 mV span	305
MM4051	Bridge transmitter	325
MM4100	Thermocouple transmitter	325
MM4100L	Thermocouple transmitter linearized	350
MM4130	Isolated thermocouple transmitter	425
MM4130L	Isolated thermocouple transmitter linearized	440
MM4300A	Limited range DC isolated transmitter	250
MM4300	DC isolated transmitter	375
MM4310	DC isolated transmitter, <50 mV Span	420
MM4380A	Wide ranging DC to DC isolated transmitter	400
MM4400	DC Summing transmitter $Y=(A+B+C+D)/4$	355
MM4401	DC Summing transmitter $Y=(A+B+C)/3$	355
MM4402	DC Summing transmitter $(A + B)/2$	355
MM4403	DC Summing / Difference transmitter $Y=(A+B+C-D)/3$	355
MM4404	DC Summing / Difference transmitter $Y=(A+B-C-D)/2$	355
MM4405	DC Difference transmitter $Y=(A-B-C-D)$	355
MM4406	DC Summing / Difference transmitter $Y=(A+B-C)/2$	355
MM4407	DC Difference transmitter $Y=(A-B-C)$	355
MM4408	DC Difference transmitter $(A - B)$	355
MM4410	DC Multiplier transmitter $(A \times B)$	445
MM4420	DC Divider transmitter (A/B)	445
MM4431	DC Power function transmitter $(Y = X^M)$	445
MM6010	Isolated AC voltage and current transmitter	400
MM7010	Frequency transmitter	410
MM7010ISO	Isolated frequency transmitter	485
MM9046	DC power supply	130

MIGHTY MODULE OPTIONS		ADD
B	(Thermocouple input only) Downscale output on burnout	\$ 20
DC Power	Inverter isolated 24VDC power (not available on MM9046)	100
	Inverter isolated 24VDC power for MM4300A, MM4380A only	40
OC	Open collector (nnp) output (MM7501 only)	0
P	(Frequency input only) Internal 10K ohms pullup resistor	0
SR100	0.1 ohm, 1%, 7 W shunt resistor	15
RT	Reverse-acting transmitter output	20
U	All circuit boards conformal coated for protection against moisture	
		(per unit)
V	Pulse output (16V, 240 ohms source) (MM7501 only)	0
ISO	Isolated output for math function modules	80

MIGHTY MODULE SERIES LIMIT ALARMS



FIELD RANGEABLE PLUG-IN LIMIT ALARMS

		PRICE
FR1000	DC Input Single Alarm with Adjustable Deadband and Jumper Selectable Latching	\$ 250
FR1020	DC Input Dual Alarm with Adjustable Deadband and Jumper Selectable Latching	340

FIXED RANGE PLUG-IN LIMIT ALARMS

SINGLE ALARM, ADJUSTABLE DEADBAND (0.5-100%)

		PRICE
MM1000	DC Voltage or Current Input	\$ 240
MM1000A	DC Voltage or Current Input	200
MM1005	4/20 mA DC Input with 24 VDC Power Supply	315
MM1200	Thermocouple Input	330
MM1400	RTD Input	330
MM1500	Strain Gauge (Bridge) Input	330
MM1600	AC Voltage or Current Input	330
MM1700	Frequency Input	330
MM1800	Potentiometer Input	330

SINGLE ALARM, LATCHING

		PRICE
MM1010	DC Voltage or Current Input	\$ 285
MM1210	Thermocouple Input	375
MM1410	RTD Input	375
MM1510	Strain Gauge (Bridge) Input	375
MM1610	AC Voltage or Current Input	375
MM1710	Frequency Input	375
MM1810	Potentiometer Input	375

DUAL ALARM, FIXED DEADBAND (0.5%)

		PRICE
MM1020	DC Voltage or Current Input	\$ 320
MM1220	Thermocouple Input	415
MM1420	RTD Input	415
MM1520	Strain Gauge (Bridge) Input	415
MM1620	AC Voltage or Current Input	415
MM1720	Frequency Input	415
MM1820	Potentiometer Input, Dual Alarm	415

MM SERIES ALARM OPTIONS

		ADD
A	(Dual Alarms only) Top-accessed screwdriver adjustable deadbands	\$ 85
B	(Thermocouple input only) Downscale output on burnout	20
D	(Dual Alarms only) Latching alarms	85
DC	Inverter isolated 24 VDC power	100
	(Not available on MM1005.)	80
E	(RTD input only) 11-pin configuration (20-pin is standard)	0
P	(Frequency input only) Internal 10 kilohms pullup resistor.	0
R	Reverse sense:	20
	Single alarms	35
	Dual alarm	45
S	(DC input only) Low input voltage (Not available with wide-range input)	15
SR100	0.1 ohm, 1%, 7 W shunt resistor	20
U	All circuit boards conformal coated (per unit)	20
V	Relay driver output	20
	Single alarm	35
	Dual alarm	35

MOUNTING HARDWARE FOR ALL MIGHTY MODULES

		PRICE
MP008	Molded plastic socket with screw terminals (8-pin)	\$ 15
MP011	Molded plastic socket with screw terminals (11-pin)	20
DMP008	Molded plastic socket, DIN-rail mount (8-pin)	15
DMP011	Molded plastic socket, DIN-rail mount (11-pin)	20
CLP-1	Hold-down clip for Mighty Modules (for use with MP008 and MP011)	15
TRK48	48" Plastic Snap-Track (Accepts MP008 and MP011)	25
HKB-HK2D-8	Explosion-proof housing with 2" dome cover and 8-pin socket (Killark HK Series). For standard-height, 8-pin Mighty Modules	295
HKB-HK2D-11	Explosion-proof housing with 2" dome cover and 11-pin socket (Killark HK Series). For standard-height, 11-pin Mighty Modules	295



SERIES SIGNAL CONDITIONERS



		PRICE
DM3801	Valve Controller	\$ 440
DM4001	RTD	415
DM4003	Potentiometer	370
DM4051	Strain Gauge (Bridge)	415
DM4130	Thermocouple	415
DM4300A	DC to DC (Standard)	290
	(High speed)	320
DM4380A	DC to DC	385
DM4391	Loop Powered Isolator	
	DM4391-1 (Single channel)	235
	DM4391-2 (Dual channel)	435
DM6010	AC RMS	440
DM7010	Frequency	415

DIN MOD SERIES OPTIONS

24VDC Power	PRICE
	\$ 65



SIGNAL CONDITIONERS



		PRICE
DR4300	DC to DC Fixed Range	\$ 255
DR4380A	DC to DC Field Rangeable	355
DR4302	Single Input, Dual Isolated 4/20 mA Output (Splitter)	280
DR1920	Back-Up Pump Controller / Alarm	360
DR6305	3-Phase, Phase Monitor Transmitter and Alarm	390



DIN MOD SERIES ACCESSORIES

DR1	35mm Symmetrical DIN Rail, 1 meter length	\$ 20
-----------	---	-------

DIS SERIES™

PROCESS INDICATORS



3.5 DIGIT DISPLAY

		PRICE
DIS471	DC Input Process Indicator with Field Replaceable Range Card	\$ 265
DIS471-24	4/20 mADC Input, Provides 24 V for external use	290
DIS472	AC Input Process Indicator	330
DIS473	RTD Input Process Indicator	330
DIS474	Thermocouple Input Process Indicator with Field Replaceable Range Card	460
DIS475	Frequency Input Process Indicator	330
DIS476	Potentiometer Input Process Indicator	330
DIS471B	DC Powered, DC Input Process Indicator	265
DIS471B-24	DC Powered 4/20 mADC Input, Provides 24 V for external use	270
DIS471B-R	DC Powered, DC Input Field Rangeable Indicator	295
DIS472B	DC Powered, AC Input Process Indicator	285

DIS SERIES I RANGE CARDS

DIS471 RANGE CARD	Range Card for DIS471	90
DIS474 RANGE CARD	Range Card for DIS474	90

DIS SERIES™

PROCESS INDICATORS



3.5 DIGIT DISPLAY

		PRICE
DIS871	DC Voltage or Current Input	\$ 475
DIS871-24	DC Input with 24 V Power Supply for Two-Wire transmitter	475
DIS872	AC Voltage or Current Input	435
DIS873	RTD Input	485
DIS874	Thermocouple Input	515
DIS875	Frequency Input	490
DIS876	Potentiometer Input	490
DIS877-1	DC Multiplier Input (AxB)	590
DIS877-2	DC Divider Input (A/B)	590
DIS877-3	DC Power Function Input (Y=X ^M)	590
DIS878	Strain Gauge (Bridge) Input	510
DIS879-1	DC Summing Input (A+B+C)/3	510
DIS879-2	DC Summing Input (A+B)/2	510
DIS879-6	DC Sum/Difference Input (A+B-C)/2	510
DIS879-7	DC Difference Input (A-B-C)	510
DIS879-8	DC Difference Input (A-B)	510

4.5 DIGIT DISPLAY

DIS971	DC Voltage or Current Input	515
DIS971-24	DC Input with 24 V Power Supply for Two-Wire transmitter	515
DIS972	AC Voltage or Current Input	480
DIS973	RTD Input	525
DIS974	Thermocouple Input	550
DIS975	Frequency Input	530
DIS976	Potentiometer Input	530
DIS977-1	DC Multiplier Input (AxB)	635
DIS977-2	DC Divider Input (A/B)	635
DIS977-3	DC Power Function Input (Y=X ^M)	635
DIS978	Strain Gauge (Bridge) Input	545
DIS979-1	DC Summing Input (A+B+C)/3	545
DIS979-2	DC Summing Input (A+B)/2	545
DIS979-6	DC Sum/Difference Input (A+B-C)/2	545
DIS979-7	DC Difference Input (A-B-C)	545
DIS979-8	DC Difference Input (A-B)	545

PROCESS INDICATOR OPTIONS

		ADD
SA *H(L)	Single Alarm	\$ 95
DA *H(L)	Dual Alarm	180
TX	Transmitter Output (isolated only)	115
B	(Thermocouples only) Downscale output on burnout	20
R	Reverse sense: Single alarm	20
	Dual alarm	35
RD	Reverse-acting display	20
RT	Reverse-acting transmitter output	20
S	(DISX71 only) Low input voltage (not available with wide range input)	55
U	All circuit boards conformal coated for protection against moisture(per unit)	20
WR	Wide range input (DC input only)	55

LP SERIES™

LOOP POWERED PROCESS INDICATORS



		PRICE
LP400	Loop Powered Display, field mount	\$ 385
LP420	Loop Powered Display, explosion-proof	600

LP400 SERIES OPTIONS

RD	Reverse-acting display	\$ 20
----------	------------------------------	-------

LP400 SERIES ACCESSORIES

		PRICE
PMK400	Pipe Mounting Kit (pipe size limited to size of strap)	\$ 45

Silver Series™

SF1000 SILVER SERIES TWO-WIRE TRANSMITTERS



		PRICE
SF1302	Low profile, Stackable, 2-wire input RTD transmitter	\$ 95

SR2000 SILVER SERIES TWO-WIRE TRANSMITTERS



		PRICE
SR2101	DC transmitter, isolated (includes range card)	\$ 265
SR2300	RTD temperature transmitter (includes range card)	210
SR2400	Thermocouple transmitter, non-isolated (includes range card)	210
SR2401	Thermocouple transmitter, isolated (includes range card)	265
SR2700	Frequency transmitter (includes range card)	230
SR2800	Potentiometer position transmitter (includes range card)	210
SR-CARD	Transmitter range card	35

TWO-WIRE TRANSMITTER MOUNTING HARDWARE & ACCESSORIES

		PRICE
CLP8500	Mounting clip (Killark, TW8000)	\$ 15
DMP2000	DIN-rail mounting plate (SF1000, SR2000, TW300)	15
DMP8500	DIN-rail mounting plate (SC5000, SC5010, TW8000)	20
DR1	35mm Symmetrical DIN Rail, 1 meter length	20
HKB-HFC	Explosion-proof housing (Killark, TW8000)	210
TRK48	PVC snap-track, 48 " length	30
TSH-A6L	NEMA-4 aluminum connection head (SF1000, SR2000, TW300)	65
XIHFCX2L	Explosion-proof housing (Adalet, SC5000)	210
XIHFGCX2L	Explosion-proof housing with window (Adalet, SC5010)	300
XJAY	Explosion-proof housing (SR2000, TW300)	150

TW SERIES™



TW300 SERIES TWO-WIRE TRANSMITTERS

		PRICE
TW301	Potentiometer input	\$ 180
TW303	RTD input	180
TW304	Thermocouple input	180

LM1000 SERIES

LEVEL MONITOR AND CONTROL



		PRICE
LM1000-N4	Level Monitor and Control, NEMA-4 Mount	\$ 570
LM1000-PM	Level Monitor and Control, Panel Mount	570

LM1000 SERIES ACCESSORIES

		PRICE
LME-N4	NEMA-4X Enclosure	\$ 185
LS1000	Level Sensor, 40 ft. Cable	1000
LS1000FL	Level Sensor with Flange, 40 ft. Cable	1025

MOSCAD INTERFACE PRODUCTS

		PRICE
SIB-V245/V453	Interface Board for Motorola™ ACE3600	\$ 355
PPS-120/24	24 VDC Power Supply for SIB-V245/V453	70
SIB-MCE-T1	Interface Board for Motorola™ MC Edge	355



WIRELESS SIGNAL CONDITIONERS, ALARMS



		PRICE
DR9011	Point to Point Wireless Transmitter (Used with DR9021)	
-01	Dual DC Input	\$ 830
-02	Strain Gauge (Bridge) Input	830
-03	RTD Input	830
DR9011R	Point to Point Wireless Repeater (Used with DR9011 and DR9021)	830
DR9021	Point to Point Wireless Receiver (Used with DR9011)	830
DR9031	Point to Point Wireless Tranceiver (Complete System Requires 2 Sets, (1) DR9031TX and (1) DR9031RX at each location)	
-01	Dual DC Input	\$ 1660
-02	Strain Gauge (Bridge) Input	1660
-03	RTD Input	1660



WIRELESS SIGNAL CONDITIONERS, ALARMS

ANTENNAS

		PRICE
4008	7" Whip, 2.1dBi Gain	\$ 50
4023	3" Omni, 2.1dBi Gain	40
4275	27" Omni with Mount Bracket, 6.0 dBi Gain	110
4241	54" Omni, 8.5dBi Gain	320
4009	3 Element Yagi, 8.0 dBi Gain	115
4078	5 Element Yagi, 11 dBi Gain	115
4079	7 Element Yagi, 12 dBi Gain	125
4025	10 Element Yagi, 14.0 dBi Gain	160
4152	Stacked 10 Element Yagi, 16.0 dBi Gain	385
4063	2.4 GHz, 16 Element Yagi, 14.0 dBi Gain	145

ACCESSORIES

		PRICE
4026	Antenna Adapter NF/NF Bulkhead	\$ 15
4024	Antenna Adapter NM/NF Bulkhead (For P/N: 4023)	30
4044	Bracket Mirror Mount NM (For P/N: 4023)	45
4045	Ground Plane GP4	10
4242	Mount Bracket (For P/N: 4241)	45
4082	Crimp Tool 400 Cable	70
4073	Coupler 2-Port 900 MHz CC850	185
4051	Coupler 4-Port 900 MHz QC850	200
4061	Coupler 4-Port 2.4 GHz QC2400	180
4062	Conn 50 Ohm N-Term (For P/N: 4073,4051,4061)	20
4022	PSP24-024S, 24 VDC 1 Amp Power Supply	130
4011	Surge Protector NM/NF w/ Bulkhead	110
4035	Surge Protector NF/NF w/ Bulkhead	110

ENCLOSURES

		PRICE
ENCL901-TX	Pre-Wired Enclosure for Wireless Transmitters (DR9011 - DR9051R)	\$ 305
ENCL901-RX	Pre-Wired Enclosure for Wireless Receivers (DR9021)	305

WIRELESS CABLES

		PRICE
CPT2	2 Ft WBC195 Cable w/ RP-SMA & NM CONN	\$ 25
CPT6	6 Ft WBC195 Cable w/ RP-SMA & NM CONN	35
CPT10	10 Ft WBC195 Cable w/ RP-SMA & NM CONN	40
C195NM-NM-2	2 Ft WBC195 Cable w/ NM & NM CONN	30
C400NM-NF-10	10 Ft WBC400 Cable w/ NM & NF CONN	70
C400NM-NF-20	20 Ft WBC400 Cable w/ NM & NF CONN	85
C400NM-NF-30	30 Ft WBC400 Cable w/ NM & NF CONN	100
C400NM-NF-40	40 Ft WBC400 Cable w/ NM & NF CONN	115
C400NM-NF-50	50 Ft WBC400 Cable w/ NM & NF CONN	135
C400NM-NF-75	75 Ft WBC400 Cable w/ NM & NF CONN	185
C400NM-NF-100	100 Ft WBC400 Cable w/ NM & NF CONN	225
C400NM-NM-10	10 Ft WBC400 Cable w/ NM & NM CONN	70
C400NM-NM-20	20 Ft WBC400 Cable w/ NM & NM CONN	85
C400NM-NM-30	30 Ft WBC400 Cable w/ NM & NM CONN	95
C400NM-NM-40	40 Ft WBC400 Cable w/ NM & NM CONN	115
C400NM-NM-50	50 Ft WBC400 Cable w/ NM & NM CONN	135
C400NM-NM-75	75 Ft WBC400 Cable w/ NM & NM CONN	185
C400NM-NM-100	100 Ft WBC400 Cable w/ NM & NM CONN	225

CUSTOMER SERVICE AND WARRANTY POLICY

IN WARRANTY PRODUCTS

Specific product warranty information may be obtained by referencing the user manual that was shipped with the product or by contacting the factory.

Lightning strikes, power surges, and all incorrect use and wiring are not covered by any warranty. Relays and antennas are not covered by any warranty.

All accessories carry a limited 90 day warranty.

NOTE: ALL WARRANTY RETURNS FOUND TO BE IN PROPER OPERATING ORDER (NO FAULTS FOUND) ARE SUBJECT TO A TEST/RECALIBRATION CHARGE OF \$50.00 PER UNIT.

OUT OF WARRANTY PRODUCTS

Product will be considered out of warranty if it is older than the specified warranty period from the date of shipment from the factory or if in the opinion of the company, it exhibits any of the following defects:

Broken or removed warranty seal.

Usage beyond rated specifications (including lightning and power surges).

Physical abuse.

Improper installation.

Customer modification to on-board circuits without express written approval from the company.

NOTE: ALL OUT OF WARRANTY REPAIRS ARE SUBJECT TO A MINIMUM CHARGE OF \$55.00, OR PARTS AND LABOR COSTS, WHICHEVER IS GREATER.

PRODUCTS NOT MANUFACTURED BY WILKERSON INSTRUMENT COMPANY INC.

All products not manufactured by Wilkerson Instrument Co. are warranted by their respective manufacturer and will carry the manufacturer's factory warranty. It is recommended that the customer first contact the original manufacturer for warranty returns. If the customer requires assistance in contacting the original manufacturer Wilkerson Instrument Company will be happy to assist.

Please do not ship non-Wilkerson Instrument Company manufactured products back to Wilkerson Instrument Company unless expressly informed to do so.

RETURNED GOODS

CALL CUSTOMER SERVICE, 1-800-234-1343, FOR RETURN AUTHORIZATION (RMA#) ON ALL RETURNS.

Wilkerson Instrument Company strives to repair and return warranty repairs within two (2) business days after receiving the product at our factory.

REPAIRS

RMA number must be referenced on all paperwork. This ensures that scheduled return dates will be met.

All shipments to Wilkerson Instrument Company must be freight prepaid; FOB destination (North America). Or DAP Destination for international customers. Return freight going out UPS/UPS Blue will be paid by Wilkerson Instrument Company on warranty items only.

Any special shipment methods are at the customer's expense and should be prearranged with Customer Service before return of items. All non-warranty repairs, modifications, and calibration shall be subject to parts, labor, and return shipping costs. All products should be adequately packaged to protect against shipment damage.

RETURNS FOR CREDIT

RMA number must be referenced on all paperwork.

Product returned for credit is subject to restocking fees of 20%, plus 10% per month from the Invoice date.

